

## BG211

### Multi-purpose, water resistant, extreme pressure (EP) bearing grease

#### Product Overview

ROCOL® BG211 is a high performance, Extreme Pressure, water resistant bearing grease designed for the effective lubrication and protection of all types of ball, roller and plain bearings.

ROCOL BG211 is ideal for applications subjected to damp, humid or wet conditions including submerged conditions.

#### Specifications

DEF STAN 91-34/3, JSD XG286, NATO G-460

NATO Stock Number 9150-99-224-8885

#### Features and Benefits

- Very good temperature resistance – ranging from -30°C to +110°C (120°C for short periods).
- Excellent resistance to water, including salt water, ensuring components is protected even in submerged conditions.
- Calcium soap technology and EP additives provides good high load performance superior to standard soap thickened lubricants.
- ROCOL BG211 has good resistance to oxidation, providing extended lubrication intervals whilst reducing equipment failure, downtime and lubricant usage.
- Excellent corrosion resistance to protect in humid, damp and even wet conditions.
- The tacky nature of ROCOL BG211 ensures it adheres strongly to the components to resist water wash-off and even tidal flow in salt water environments.

#### Directions for Storage and Use

- ROCOL BG211 can be applied manually, by grease gun, keg pump or by other methods suitable for an NLGI No. 2 grease.
- Compatible with other soap thickened greases. However, for best results the previous lubricant should be removed prior to application.
- The storage temperature should be controlled between +1°C and +40°C.
- Shelf life is 4 years from date of manufacture.

#### Typical Applications

ROCOL BG211 is designed for all types of ball, roller and plain bearings found in all types of damp, humid or wet industrial applications. Particularly suitable for use in salt water environments.

ROCOL BG211 is ideal for all industries where a high performance, water resistant lubricant is required such as water treatment, quarries, marine, docks, agriculture, construction, textile, and most other industries.

- ROCOL BG211 excels in applications such as scrapers, rakes, dockside cranes, water pumps, boat trailers and similar applications where bearings, pins, bushes, slides etc are subjected to extreme wet conditions.

#### Pack Sizes

Please Call +44(0) 1132 232 2600

## BG211

Multi-purpose, water resistant, extreme pressure (EP) bearing grease

Property	Test Method	Result
Appearance	Visual	Brown grease
NLGI No.	IP 50 – ASTM D217	2
Base Type	N/A	Severely refined mineral oil
Base Fluid Viscosity at 40°C	IP 71	110cSt
Base Fluid Viscosity at 100°C	IP 71	8.5cSt
Thickener	N/A	Calcium soap
Temperature Range	N/A	-30°C to +110°C (+120°C short periods)
4 Ball Weld Load	IP 239 – ASTM D2596	225kg
4 Ball Mean Hertz Load	IP 239 – ASTM D2596	45kg
Timken ‘OK’ Load	IP 326 – ASTM D2509	35 lb
Emcor Corrosion Test	IP 220	0:0
Copper Corrosion Test	IP 112 – ASTM D130	1a
Water Washout Test	IP 215 – ASTM D1264	3%

Values quoted above are typical and do not constitute a specification.

### Safety Data Sheets

Safety data sheets are available for download from our website [www.rocol.com](http://www.rocol.com) or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 2 Date: 05-20

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTORS  
IN PEOPLE