

FLO-LINE® 700



High temperature chain oil

Product Overview

ROCOL® FLO-LINE 700 is a new generation lubricant specially designed for BRUCKNER sliding chain systems. ROCOL FLO-LINE 700 has been developed in conjunction with BRUCKNER to meet the requirements of higher speed and heavier loaded machines.

ROCOL FLO-LINE 700 is formulated from a combination of synthetic esters and a special antioxidant package which ensures the highest performance in terms of thermal stability, low evaporation loss and minimal deposit formation.

Features and Benefits

- ROCOL FLO-LINE 700 has a special antioxidant combination that gives a longer wet film life with lower deposit and varnish formation.
- ROCOL FLO-LINE 700 demonstrates a low viscosity increase at elevated temperatures eliminating the risk of tube blockage on automatic lubrication systems.
- The superior anti-wear properties of ROCOL FLO-LINE 700 minimises frictional heat generation on rail systems allowing higher production speeds.
- ROCOL FLO-LINE 700 penetrates into the links and pins providing high performance lubrication in the highest potential wear areas.
- The excellent frictional properties give reduced power consumption on chain drive units.
- Low evaporation and usage gives good economy in use.
- Low fuming provides a clean working environment.

Directions for Storage and Use

- ROCOL FLO-LINE 700 should be stored unopened in the original container.
- The storage temperature of ROCOL Flo-Line 700 should be between +1°C and +40°C.
- If ROCOL FLO-LINE 700 is stored in accordance with the above guidelines, shelf life is 3 years from date of manufacture.
- ROCOL FLO-LINE 700 has been designed for application by automatic lubricators and should be used in accordance with the lubricator manufacturer's instructions.
- The compatibility of ROCOL FLO-LINE 700 with other chain oils should be checked before mixing.

Specifications

- FLO-LINE 700 does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- NSF H2 registered - 143333

Pack Sizes

Pack Size	Part Code
20L	22705
200L	22709



FLO-LINE® 700

High temperature chain oil

Property	Test Method	Result
Colour	Visual	Yellow liquid
Base Oil Type	N/A	Synthetic ester mixture
Kinematic Viscosity:		
cSt @ 40°C	IP 71 (ASTM D445)	240
cSt @ 100°C	IP 71 (ASTM D445)	22
Viscosity Index	ASTM D2270	100
Temperature range	N/A	10°C to 250°C
Moisture Content (ppm)	Karl-Fischer	<300
Density (g/cm ³)	N/A	0.98
Flash Point (°C) COC	ASTM D93	>300
Copper Corrosion	IP 112 – ASTM D130	1b
Evaporation Test 200°C % Loss	Oven	2.6
Oxidation Point (°C)	DSC Onset	325

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 3 Date: 10-17

T +44 (0) 113 232 2600
 F +44 (0) 113 232 2740
 E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd

