

Performance you can trust



FOODLUBE® 1500 Spray

Food grade, multipurpose, chain and press lubricant in aerosol

Applications

ROCOL FOODLUBE 1500 Spray is a high-viscosity, non-toxic, water-resistant lubricating aerosol designed primarily for the effective lubrication of all types of chains & presses operating in food, pharmaceutical and other clean environments.

FOODLUBE 1500 Spray is an excellent all-round lubricating fluid containing additives to boost performance and improve adhesion, creating high tack and low drip fluid. It also offers excellent water wash off resistance and corrosion protection necessary.

- Tablet Presses
- Overhead Chains
- Hoists

Features and Benefits

- Metal detectable plastic components (aerosol caps & actuators) capable of detection by most metal detection equipment.
- Excellent wide temperature range of -20°C to +160°C (+180°C for short periods).
- Excellent penetration and load carrying properties ensuring that the product lubricates and protects.
- Provides a water displacing, highly adhesive film with excellent water wash off resistance and corrosion protection.
- Excellent oxidation stability resulting in extended relubrication intervals and a reduction in lubricant usage.
- **T** +44 (0) 113 232 2600
- E <u>customer.service@rocol.com</u>

www.rocol.com

Usage Guidance

Shake thoroughly before spraying. Hold can upright and apply from a distance of 15-30 cm, covering the area thoroughly.

Storage Guidance

Storage temperature should be kept below +50°C and out of direct sunlight.

Shelf life is 5 years from date of manufacture.

Approvals and Certifications

- NSF H1 Registered 165034
- ISO 21469
- Halal Certified
- Kosher Certified
- Vegan Society Certified
- Manufactured from only FDA listed ingredients: FDA Group 21 CFR 178.3570
- Does not contain mineral oil hydrocarbons, nut oils or genetically modified ingredients.

Pack Sizes

Part Code	Pack Size
15520	400 mL



ROCOL A Division of ITW Limited ROCOL House, Swillington, Leeds, LS26 8BS, UK VAT Number: 742053167 Registered Company No: 00559693 Registered Office: Saxon House, 2-4 Victoria Street, Windsor, England, SL4 1EN



Performance you can trust



FOODLUBE 1500 Spray

Food grade, multipurpose, chain and press lubricant in aerosol

Parameter	Test Method	Value
Appearance	Visual	Pale yellow, almost colourless, liquid
Base Type	N/A	Polyalphaolefin
Propellant	N/A	Hydrocarbon
Base Fluid Viscosity at 40°C		1500cSt
Temperature Range – Continuous	N/A	-20°C to +160°C
Temperature Range – Short	N/A	Up to 180°C
Periods		
4-Ball Wear Scar – 40kg for 1		0.36mm
hour		
Metal Detection:		
Aerosol Cap	Equivalent sphere size	>3.0mm
Actuator	Equivalent sphere size	>3.0mm

Safety Datasheets

These are available at <u>https://www.rocol.com/datasheets</u>. For further assistance, please contact us via the ROCOL website or using the details below.

Note

The information in this Technical Datasheet is informed by our experience and feedback from industry. There are many variables outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility. Values quoted are typical and do not constitute a specification.

If you'd like to discuss the suitability of any ROCOL solution for your system, please get in touch.

T +44 (0) 113 232 2600 E customer.service@rocol.com

www.rocol.com

ISO 14001 ISO 9001 AS/EN ISO/IEC ISO 45001 Quality Management 9100 27001 ealth and Safet Aviation Space and Defence Management on Security Managemer CERTIFIED CERTIFIED CERTIFIED CERTIFIED CERTIFIED

ROCOL A Division of ITW Limited ROCOL House, Swillington, Leeds, LS26 8BS, UK VAT Number: 742053167 Registered Company No: 00559693 Registered Office: Saxon House, 2-4 Victoria Street, Windsor, England, SL4 1EN