

Technical Data

FOODLUBE® Spray Grease

Food Grade, Extreme Pressure (EP) grease in an aerosol



Nonfood Compounds
Program Listed: H1
ISO 21469 Certified

Description

ROCOL® FOODLUBE SPRAY GREASE is FOODLUBE UNIVERSAL 2 in an aerosol can for convenient application. It is a white, non-toxic lubricant designed for the effective lubrication and protection of ball, roller and plain bearings, slides, pins, linkages and bushes operating in food, pharmaceutical and other clean environments.

FOODLUBE SPRAY GREASE is an excellent all round lubricating aerosol offering excellent water wash-off resistance and corrosion protection necessary for lubricants used in food, pharmaceutical and other clean environments.

FOODLUBE SPRAY GREASE is also available as a bulk grease called FOODLUBE UNIVERSAL 2.

Applications

- Precision Bearings
- Plain Bearings
- Bushes
- Slides
- Pins
- Links

Approvals / Specifications

- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- Manufactured from only FDA listed ingredients:
 - FDA Group 21 CFR 178.3570
- NSF H1 registered – 138048
- ISO 21469
- Halal certified
- Kosher certified
- Vegan Society Approved
- Rocol unique TPM number – 31

Features & Benefits

- Excellent wide temperature resistance of -50°C to +160°C.
- Exhibits outstanding EP performance with a weld load of 620 kg.
- Highly resistant to water wash-off and offers excellent corrosion protection.
- It has excellent oxidation stability resulting in extended relubrication intervals and a reduction in lubricant usage.
- Excellent all round, long life lubricant fortified with PTFE for improved lubricity and performance.
- Metal detectable plastic components (aerosol caps and actuators) capable of detection by most metal detection equipment.
- Blue spray nozzle for easy identification as a food safe product.

Directions For Use

Shake the FOODLUBE Spray Grease thoroughly before use.

Ensure adequate ventilation

Apply FOODLUBE Spray Grease from a distance of 15-30 cm (6-12 inches).

The storage temperature should be kept below +50°C, and the storage area should be out of direct sunlight.

Shelf life is 5 years from date of manufacture.

Further Information

For pack sizes, part codes and safety data sheets please visit www.rocol.com or get in touch with our customer service team who will be happy to help: customer.service@rocol.com

Technical Data

FOODLUBE® Spray Grease

Food Grade, Extreme Pressure (EP) grease in an aerosol



Nonfood Compounds
Program Listed: H1
ISO 21469 Certified

Property	Test Method	Result
Appearance	Visual	Thin, white tenacious grease
NLGI No.	IP50 – ASTM D217	2
Base Type	N/A	Polyalphaolefin
Base Fluid Viscosity at 40°C	IP71 – ASTM D445	47cSt
Base Fluid Viscosity at 100°C	IP71 – ASTM D445	8cSt
Thickener	N/A	Aluminium complex soap
Solids	N/A	White, non-toxic solids/PTFE
Solvent	N/A	Hydrocarbon
Propellant	N/A	LPG (hydrocarbon)
Temperature Range	N/A	-50°C to +160°C
4-Ball Weld Load	IP239 – ASTM D2596	620kg
SKF ROF Bearing Life	N/A	1100 hours
Corrosion Test - Emscor	IP220	0:0
Copper Corrosion Test	IP112 – ASTM D130	1b
Water Washout Test	IP215 – ASTM D1264	<2%
Drop Point	IP132 – ASTM D566	>230°C
Metal Detection:		
Aerosol Cap	Equivalent sphere size	>3.0mm
Actuator	Equivalent sphere size	>3.0mm

Values quoted above are typical and do not constitute a specification.

Issue 6 Date: 12/21

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740
E customer.service@rocol.com www.rocol.com
ROCOL House, Swillington, Leeds LS26 8BS

ROCOL® A division of ITW Ltd

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

