

FOODLUBE® Sugar Dissolving Fluid

Food grade fluid for dissolving sugar and fondants from all surfaces



Nonfood Compounds
H1 Registered
ISO 21469 Certified
NSF 537 PFAS-Free Certified

Description

FOODLUBE Sugar Dissolving Fluid is a non-toxic fluid that dissolves sugar and fondants from all types of applications commonly found in food, pharmaceutical and other clean environments. It leaves a corrosion protective film on the surface to protect it from attack.

FOODLUBE Sugar Dissolving Fluid also leaves a durable film on the surface for lubrication and to resist further contamination.

FOODLUBE Sugar Dissolving Fluid is supplied in a hand trigger pack for accurate application particularly where aerosols cannot be used due to risk or preference. A bulk version is also available for refilling the trigger pack.

Features and Benefits

- FOODLUBE Sugar Dissolving Fluid offers a wide temperature resistance of +5°C to +95°C.
- FOODLUBE Sugar Dissolving Fluid rapidly dissolves and removes sugars and fondants from the surfaces to ensure components remain operational.
- FOODLUBE Sugar Dissolving Fluid penetrates rapidly to leave a light, durable lubricating film on the surface.

Usage Guidance

Shake the container thoroughly before use. FOODLUBE Sugar Dissolving Fluid can be applied directly from the hand trigger pack or by spraying, dipping, brush or oilcan.

FOODLUBE Sugar Dissolving Fluid should be applied directly to the sugar or fondant deposits.

FOODLUBE Sugar Dissolving Fluid is not suitable for chocolate deposits.

Storage Guidance

The storage temperature should be controlled between +1°C and +40°C. Shelf life is 2 years from date of manufacture.

Approvals and Certifications

- NSF H1 registered - 122877
- ISO 21469
- NSF 537 - PFAS Free
- Halal certified
- Kosher certified
- ROCOL unique TPM number - 21
- Manufactured from only FDA listed ingredients: FDA Group 21 CFR 178.3570
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.

Pack Sizes

Part Code	Pack Size
15110	500 mL
15116	5 L

T +44 (0) 113 232 2600

E customer.service@rocol.com

www.rocol.com

ROCOL A Division of ITW Limited

ROCOL House, Swillington, Leeds, LS26 8BS, UK

VAT Number: 742053167

Registered Company No: 00559693

Registered Office: Saxon House, 2-4 Victoria Street, Windsor, England, SL4 1EN





Technical Datasheet

Performance you can trust

T +44 (0) 113 232 2600

E customer.service@rocol.com

www.rocol.com

ROCOL A Division of ITW Limited

ROCOL House, Swillington, Leeds, LS26 8BS, UK

VAT Number: 742053167

Registered Company No: 00559693

Registered Office: Saxon House, 2-4 Victoria Street, Windsor, England, SL4 1EN



Revision Date: 0825

Template: 2507

FOODLUBE Sugar Dissolving Fluid

Food grade fluid for dissolving sugar and fondants from all surfaces

Parameter	Test Method	Value
Appearance	Visual	Water white - slightly hazy
Base type	N/A	Water based synthetic fluid
Viscosity	IP 71 - ASTM D445	Non-viscous
Odour	N/A	Barely perceptible
Temperature range	N/A	+5 °C to +95 °C
Flash point	ASTM D92	> 150 °C
Specific gravity	N/A	1
pH	N/A	8-9

Safety Datasheets

These are available at <https://www.rocol.com/datasheets>. For further assistance, please contact us via the ROCOL website or using the details below.

Note

The information in this Technical Datasheet is informed by our experience and feedback from industry. There are many variables outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility. Values quoted are typical and do not constitute a specification.

If you'd like to discuss the suitability of any ROCOL solution for your system, please get in touch.

T +44 (0) 113 232 2600

E customer.service@rocol.com

www.rocol.com

ROCOL A Division of ITW Limited

ROCOL House, Swillington, Leeds, LS26 8BS, UK

VAT Number: 742053167

Registered Company No: 00559693

Registered Office: Saxon House, 2-4 Victoria Street, Windsor, England, SL4 1EN

