

Technical Data

TUFLUBE EXTREME

Heavy Duty Crane Boom Grease

Description

TUFLUBE EXTREME is an extreme heavy duty, versatile and highly adhesive grease formulated for telescopic crane booms.

Protects and lubricates booms in the wettest and most corrosive conditions.

TUFLUBE EXTREME is a highly adhesive, high load grease which will prevent crane booms seizing under arduous conditions.

Ensures smooth movement between wear pads and boom sections.

Applications

- Booms
- Telescopic arms
- Open Gears
- Rollers
- Slew Rings
- Cantilevers
- Winches
- Joints & Couplings
- Tracks and Rails
- Penstocks, sluice gates, winding gears or locks
- Water treatment facilities

Features & Benefits

- High load carrying capability
- Water resistance including salt water
- Light coloured grease for high visibility and ease of inspection.
- Highly adhesive
- Reduces Friction
- Prolongs maintenance intervals and re-lubrication frequencies
- Reduces downtime
- Extends equipment life
- Ensures smooth movement
- Provides excellent lubricity

Directions For Use

TUFLUBE EXTREME should be stored in its unopened original container.

For best practice, storage temperature of should be controlled to between +1°C and +40°C.

Shelf life is 3 years from date of manufacture

The minimum application temperature for TUFLUBE EXTREME is 0°C.

Can be applied by hand or automatic lubrication equipment

Further Information

For pack sizes, part codes and safety data sheets please visit www.rocol.com or get in touch with our customer service team who will be happy to help: customer.service@rocol.com

Technical Data

TUFLUBE EXTREME

Heavy Duty Crane Boom Grease

Property	Test Method	Result
Appearance	Visual	Smooth, off white grease
NLGI No.	IP 50 – ASTM D217	1/2
Base Type	N/A	Severely refined mineral oil
Base Fluid Viscosity at 40°C	IP 71	250 cSt
Thickener	N/A	Aluminium Complex
Temperature Range	N/A	-50°C to +160°C
4 Ball Weld Load	IP 239 - ASTM D2596	800kg

Values quoted above are typical and do not constitute a specification.

Issue 1 Date: 11/20

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740
 E customer.service@rocol.com www.rocol.com
 Rocol House, Swillington, Leeds LS26 8BS

ROCOL® A division of **ITW** Ltd

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

