

Performance you can trust

ULTRACUT® EVO 260 High Performance Extreme Pressure Long Life Cutting Fluid

ULTRACUT EVO 260 is a high performance extreme pressure soluble oil water mix cutting fluid specially formulated to give a long predictable sump life. It is designed to give superior performance in severe cutting operations on a wide range of ferrous and non-ferrous metals including difficult to machine alloys. The combination of outstanding extreme pressure performance and long sump life permits increased machining rates and cost efficiency.

Features

- Excellent residual corrosion protection.
- Optimum tool life.
- Promotes excellent surface finish.
- Increases production rates.
- Suitable for severe machining applications.
- Suitable for use with most metals.
- Inherently resistant to degradation.
- Long and predictable sump life.
- Low foaming.
- Rejects tramp oil.
- Ideal for individual and central cutting fluid systems.
- Contains no biocides or skin sensitisers.
- Pleasant and safe to use.

Directions for Use

Recommended dilution: ULTRACUT EVO 260 should be used between 20:1 and 40:1 depending on the severity of the operation, workpiece material and water hardness. To ensure dilution accuracy, it is preferable to use a Rocol® Automatic Fluid Mixer. For manual mixing, add the concentrate to water at the recommended dilution ratio, stirring continuously.

It is advisable to use the appropriate Rocol ULTRAGUARD® Machine Tool Care product at fluid changeovers. Optimum fluid life is obtained by adequate initial machine cleaning, correct dilution control and regular maintenance of fluid, particularly prior to weekends and shutdown periods.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



Performance you can trust

ULTRACUT EVO 260

Appearance	Clear amber liquid forming a white emulsion when mixed with water.
Odour	Mild
pH	9.4 at 25:1
Density at 20°C	0.99 g/cm ³
Storage	Store at normal ambient temperature (5 to 30°C)
Pack Sizes – Part Codes	20 ltr - 51263 200 ltr - 51269 1000 ltr - 51270

Refractometer Calibration:

Dilution ratio	10:1	20:1	30:1	40:1	50:1
Refractometer reading	9.5	5.0	3.4	2.5	2.0

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 2 Date: 06-15

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd

